

# Hydraulic Torque Wrenches

## Square Drive Wrench

- 50 - 50,000 ft. Lbs.
- Compact Design/Uni-body Housing
- Construction of Aluminum/Titanium and Steel Alloy
- Anti-Jam Torque Release Lever



TOOL MODEL	SQUARE DRIVE SIZE inches	TORQUE				WEIGHT	
		Ft. Lbs.		Nm		lbs	kg
1	3/4"	200	1340	271	1817	3.8	1.9
3	1"	480	3230	651	4379	7.8	3.9
5	1-1/2"	835	5590	1132	7578	15	7.5
8	1-1/2"	1200	8000	1627	10,845	23	11.5
10	1-1/2"	1755	11,520	2379	15,617	26.8	13.4
20	2-1/2"	2960	19,760	4013	26,787	36	18
25	2-1/2"	3960	25,890	5368	35,096	62	31
50	2-1/2"	7875	52,500	10,675	71,169	96	48

## Low Profile Wrench



- 100 - 30,000 ft. Lbs. -
- Compact Design -
- Anti-jam Torque Release Lever -

TOOL MODEL	RATCHET Link HEX SIZE		TORQUE				WEIGHT	
			Ft. Lbs.		Nm		lbs	kg
	inches	mm	min	max	min	max		
2	3/4"-2-3/4"	19 - 70	255	1710	346	2318	4	2
4	1"- 3-1/8"	25 - 80	580	3855	786	5226	9	4
8	3-5/8"-4-1/4"	41 - 105	1143	8151	1549	11,049	19	9
14	2-1/2"-5-3/8"	60 - 130	2010	13,400	2725	18,165	33	15
30	3-9/16"- 7-7/8"	90 - 200	4770	31,800	6466	43,108	78	35